

V-TEK

Effective Solution to Security Needs



2Easy-IX IP
Network Video Intercom System

Ordering Catalogue(2022)

V-TEK

Guangzhou Video-Tech Electronics Co., Ltd

201/Building 1, No. 8 Lianhuayan Road,
Huangpu District, Guangzhou, China

T 0086 / 20 / 32382021

E info@v-tec.com.cn

www.v-tec.cn



> 2Easy-IX IP Network Video Intercom System

- **HD Input and Display**
720P door station camera, 1024 *600 TFT
- **LAN & WLAN hybrid network**
Wire or wireless chose for home monitor connection
- **Wi-Fi call divert with VDP Connect APP**
Home Wi-Fi connectivity IPC surveillance from APP
- **Wider ONVIF IPC compatibility**
Support H264 & H265

> Product range

- Villa door station
- Modularized apartment station
- TFT touch screen apartment station
- 7" high resolution monitor
- Touch screen operation
- With Wi-Fi connectivity





General Layout of IP system

IP Outdoor Stations



IP Monitors under different application



LAN Net mode

WLAN Net mode

Wired lan connection

Wireless connection

Wire/wireless connection

> Contractor



• **Specialized**

Expert in 1~256 IP devices project



• **Customizable**


Interface, language, logo



• **Integrate**

IP camera, Elevator, Alarm

> Installer



• **One Cable for ALL**

Support IEEE 802.3 af PoE Lan switch, one cable for all connect.



• **Offline IP auto-config**

Automatically self-config IP address without DHCP (within 256 devices), simple as traditional door phone.



• **Remote config**

Onsite device management or IX-device PC tool @local/ cloud

> End user



• **Call Divert**

Pick up call and unlock from mobile phone



• **Lift Control**

Calling and Landing pick-up



• **IPC Surveillance**

PiP in calling, Quad split

***New IPS TFT**

for high resolution & better experience



800*480 Pixel VS 1024*600 Pixel

- 1024*600 pixel
- Wider viewing angle
- More consistent and higher contrast
- Faster response for touch



Any angle, more clear

PC tool management



- Free PC software
- Remote config

***Widely compatible IPC**

For Mainstream IP camera in the market (support ONVIF)



- Support IP camera with H.264 or H.265
- Standard 1080P
- Monitoring via APP in mobile phone
- Advanced video experience: Quad & PiP

Quad view

- In monitor mode
- Enable to display four images at a screen
- Switch seamlessly between One-view and Quad-view
- Free to zoom in any views




PiP view

- In call mode
- Picture in picture to avoid dead corner
- Enable to watch both view from door station and IP camera
- Swap the two images by a simple touch




System wiring and applications

> Standard wired wiring




> Standard wireless wiring




*Choose feasible MESH/PLC to strengthen communication stability and reliability


> Standard hybrid wiring




> Typical wiring in standalone building



> Typical wiring in villa





GUANGZHOU VIDEO-TECH ELECTRONICS CO.,LTD

- Founded in 1999
- Specialized in door-entry system
- Unique system with V-TECH characters
- Fully owned leading technology
- Excellent agency system
- High quality products

E10

R&DM

CE FC

RoHS REACH

2EASY WIKI



Product Photos with Product Information.....P12-23

- Villa door station IX610P12
- Apartment modularized door station IX821.....P14
- Apartment door station IX850.....P16
- Indoor monitor 7" IX471S.....P18
- Indoor monitor 7" IX482.....P20
- Indoor monitor 7" IX47S.....P22

Order information.....P24

Appendix and Notes.....P28




Description

IP system single button villa door station with aluminum front cover


Features

- 720P Wide angle fisheye camera
- Aluminum front cover
- Auto sensor night vision LED
- Big back-lit push button
- Simple & compact design
- PoE power supply
- IP 65 rate

Dimension and mount



Terminal Description



Lan connector

Use to connect the indoor station to the network.

Terminal connector

Use to connect external devices to the indoor station.

Packing Information

Single Package



Dimensions: 166(H)×103(W)×60(D)mm

Gross Weight: 0.53Kg

Carton Package



Carton: 340 (H)×530 (W)×258 (D)mm

Quantity: 32PCS






Description

IP apartment system color fisheye camera modularity outdoor station.

Features

- 720P Wide angle fisheye camera
- Stainless steel with fingerprint proof
- Auto sensor night vision LED
- Modularization for flexible use(2-6 modules)
- Surface and flush mounting chose
- IP 65 rate

Terminal Description




Lan connector

Use to connect the indoor station to the network.


Terminal connector

Use to connect external devices to the indoor station.

Dimension and mount



Standard specification



Packing Information

Single Package



Dimensions: 171(H)X420(W) X98(D) mm

Gross Weight: 1.56Kg

Carton Package



Carton: 265(H)X415 (W)X360(D)mm

Quantity: 7PCS




Description

IP apartment system color fisheye camera 5 inch digital color TFT Touch Screen outdoor station with stainless front panel

Features

- 720P Wide angle fisheye camera;
- Stainless steel front panel, fingerprint proof;
- 5-inch TFT monitor(800x480 pixels);
- Touch screen operation(5mm tempered glass);
- PoE power supply;
- RFID Proximity card access control;
- Password access control with touch keypad;
- Auto sensor night vision LED;
- Flush or surface mount optional;
- IP 65 rate

Terminal Description



USB connector

SD card connector


Lan connector

Use to connect the indoor station to the network.


Terminal connector

Use to connect external devices to the indoor station.

Dimension and mount



Standard specification



Packing Information

Single Package



Dimensions: [IX850] 118(H)X303(W) X62(D) mm

[IX850F] 145(H)X365(W) X75(D) mm

Gross Weight: [IX850] 1.38Kg

[IX850F] 1.56Kg


Carton Package



Carton: 265(H)×415 (W)×360(D)mm

Quantity: [IX850] 12PCS

[IX850F] 7PCS




Description

IP system 7" touch screen monitor with memory & recording and Wi-Fi connectivity.


Features

- 7" TFT screen (1024 * 600)
- Touch screen operation
- Slim and ultra flat design
- Super thin glass front panel
- Full duplex communication
- Embedded Wi-Fi antenna for wireless connectivity
- Short cut setting & Favorite setting
- Support slave handset connection
- Support SIP call divert to mobile phone
- Support multiple screens / Quad for monitoring
- Support PiP view when called by door station
- Support online updates and served as a on site tool
- Support multi-languages (customization)
- Support Alarm functions (customization)

Dimension



Terminal Description



2 wire connector
Reserved for 2 wire system.

Terminal connector
SW+,SW-: Extra door bell call button connection port.
P+,P-: Use to connect 24V local power supply (HDR-30-24).

Alarm zone

Lan connector
Use to connect the indoor station to the network.

Packing Information

Single Package



Dimensions: 165(H)×240(W)×39(D)mm
Gross Weight: 0.73Kg

Carton Package



Carton: 258 (H)×530 (W)×340 (D)mm
Quantity: 24PCS




Description

IP system 7" touch screen monitor with memory & recording.


Features

- 7" IPS full view angle TFT screen (1024 * 600)
- Touch screen operation
- Full duplex communications
- Embedded Wi-Fi antenna for wireless connectivity
- Short cut setting & Favorite setting
- Support slave handset connection
- Support private call by a handset add-on
- Support SIP call divert to mobile phone
- Support multiple screens / Quad for monitoring
- Support PiP view when called by door station
- Support online updates and served as a on site tool
- Support multi-languages (customization)
- Support Alarm functions (customization)

Dimension



Terminal Description



Terminal connector
 SW+,SW-: Extra door bell call button connection port.
 P+,P-: Use to connect 24V local power supply (HDR-30-24).

Alarm zone

2 wire connector
 Reserved for 2 wire system.

Lan connector
 Use to connect the indoor station to the network.

Packing Information

Single Package



Dimensions: 165(H)×240(W)×39(D)mm
 Gross Weight: 0.55Kg

Carton Package



Carton: 258 (H)×530 (W)×340 (D)mm
 Quantity: 24PCS



Description

IP system 7" touch screen monitor with memory & recording.


Features

- 7" TFT screen (1024 * 600)
- Touch screen operation
- Slim and ultra flat design
- Super thin glass front panel
- Embedded Wi-Fi antenna for wireless connectivity
- Short cut setting & Favorite setting
- Support slave handset connection
- Support SIP call divert to mobile phone
- Support multiple screens / Quad for monitoring
- Support PiP view when called by door station
- Support online updates and served as a on site tool
- Support horizontal and vertical mounting
- Support multi-languages (customization)
- Support Alarm functions (customization)

IX47S with black housing




Dimension



*Support vertical mounting with same bracket

Terminal Description



Alarm zone

Terminal connector

SW+,SW-: Extra door bell call button connection port.

P+,P-: Use to connect 24V local power supply (HDR-30-24).

2 wire connector

Reserved for 2 wire system.

Lan connector

Use to connect the indoor station to the network.

Packing Information

Single Package



Dimensions: 166(H)×244(W)×40(D)mm

Gross Weight: 0.68Kg

Carton Package



Carton: 258 (H)×530 (W)×340 (D)mm






Quantity: 24PCS

Ordering list of Outdoor Stations

• IX610

	Product code	Model No.	Description	Qty of package
	P23991301	IX610	Single family villa door station with fisheye camera	32 pcs

• IX821 Series


	Product code	Model No.	Description	Qty of package
	P31219601	IX821/VD	Video controller module	54 pcs
	P31219540	821/M4	4 users physical call button module	54 pcs
	P31219411	821/BL	Blind module Blind panel for single empty	54 pcs
	P31219404	821/MK	Digital keypad module for code unlock & room number calling	54 pcs
	P31219405	821/DR	Proximity unlock and Dot-matrix display module	54 pcs

• IX850 Series



	Product code	Model No.	Description	Qty of package
	P31229001	IX850	Apartment door station for surface mounting	12 pcs
	P31229002	IX850F	Apartment door station for flush mounting	7 pcs

Ordering list of Indoor Monitors


• IX482

	Product code	Model No.	Description	Qty of package
	P29482001	IX482	7" full digital IP monitor with touch screen, memory, Wi-Fi connectivity	24 pcs

• IX47S

	Product code	Model No.	Description	Qty of package
		IX47S-W	7" full digital IP monitor with touch screen, memory, Wi-Fi connectivity, white housing	24 pcs
		IX47S-B	7" full digital IP monitor with touch screen, memory, Wi-Fi connectivity, black housing	24 pcs

• IX471S

	Product code	Model No.	Description	Qty of package
	P20471004	IX471S	7" full digital IP monitor with IPS touch screen, memory, Wi-Fi connectivity	24 pcs









Ordering list of Accessories

• 821 mountings

	Product code	Model No.	Description	Qty of package
	P31219418	821S-2X1	2-module surface mounting rainy cover box with front panel	8 pcs
	P31219414	821F-2X1	2-module front frame with flush mounting box	8 pcs
	P31219419	821S-2X2	4-module surface mounting rainy cover box with front panel	6 pcs
	P31219415	821F-2X2	4-module front panel with flush mounting box	6 pcs
	P31219416	821S-3X1	3-module surface mounting rainy cover box with front panel	7 pcs
	P31219412	821F-3X1	3-module front frame with flush mounting box	7 pcs
	P31219417	821S-3X2	6-module surface mounting rainy cover box with front panel	6 pcs
	P31219413	821F-3X2	6-module front frame with flush mounting box	6 pcs

Ordering list of Accessories

• Peripherals

	Product code	Model No.	Description	Qty of package
PoE switch				
 	P34093059	POE-4P	4 Port PoE switch(Power-over-Ethernet)	16 pcs
	P34093060	POE-8P	8 Port PoE switch(Power-over-Ethernet)	6 pcs
Actuator				
 	P36007090	IX-RLC	Relay control module	28 pcs
	P36001101	IX-LIFT	Lift control module, 14 relays	28 pcs
Guard Unit & IP camera				
 	P29471210	IX471-GL	Guard unit, 7inch touch screen	10 pcs
	P69010052	IPC-B	IP camera, Onvif	10 pcs
Handset				
 	P24904301	IX-DJ401	Handset gadget for private talk, with a dedicated mounting bracket	28 pcs
	P24904101	IX-DJ4A	Audio Slave Handset	28 pcs

IP system

- Power Source: Power-over-Ethernet (IEEE 802.3af Class 0)
- Network Interface: 10 BASE-T / 100 BASE-TX Ethernet (RJ-45)
- Network Protocols: IPv4, IPv6, TCP, UDP, SIP, HTTP, HTTPS, RTSP, RTP
- Audio: G711u, 8K 16bits
- Video: H.264/H.265 200K-2M
- Communication: Hands-free
- Camera Type: 1/3.7" Ultra Sense, ISP with 77dB WDR
- Wire Type: Cat-5e or Cat-6
- Wiring Distance: 100m (Approx. 330')

A series of horizontal dotted lines for taking notes, spanning the width of the page.